

## N-BM22 Face

LIFT UP STYLE QUOTIENT



Face



Finger



RFID



WiFi



LAN



USB



Access Control

## Multi-Bio Attendance and Access Control

### Storage Capacity

|                 |          |
|-----------------|----------|
| Face Capacity   | 1000     |
| Finger Capacity | 10,000   |
| Card Capacity   | 10,000   |
| Max User        | 10,000   |
| Password        | 10,000   |
| Log Capacity    | 2,00,000 |

### Features

High-Speed and Accurate Fingerprint Identification

Face, Fingerprint, Card, Password authentication

output relay for door open.

Supremely low Electric energy consumption.

Highly reliable and durable.

Comprehensive software development kit(SDK) is available for development and integration.



### N-BM22 Face

"N-BM22 Face tops the list in matter of style and decency it adds to your place."

# N-BM22 Face

## Communication Interface

|               |                          |
|---------------|--------------------------|
| Communication | WIFI, RS485, TCP/IP, USB |
|---------------|--------------------------|

## Biometric

|                   |                            |
|-------------------|----------------------------|
| Push Data         | YES                        |
| Sensor type       | 500 DPI                    |
| FAR               | 0.01%                      |
| FRR               | 0.001%                     |
| OS                | Linux                      |
| Verification Time | <=1 second                 |
| RF card options   | 125kHz EM (Standard) /     |
|                   | 13.56MHz Mifare (Optional) |

## Audio/Visual

|                   |                                       |
|-------------------|---------------------------------------|
| Display           | Capacitive Touch Screen               |
| Voice instruction | 16-bit Hi-Fi voice & sound indication |
| Language          | English                               |

## Access control

|                                  |                                  |
|----------------------------------|----------------------------------|
| Wiegand in & out                 | YES                              |
| Relay                            | YES                              |
| Anti Passback                    | YES                              |
| Standard Access Control Function | 255 Time Zone, Anti-passback     |
|                                  | Multi-identification Verify mode |
| Support                          | RS485 Reader, Wiegand Reader,    |
|                                  | Remote, Push Button, No Touch    |

## Power & Enviroment

|                       |                  |
|-----------------------|------------------|
| Operating Temperature | 0°C ~ 50°C       |
| Power                 | 12V DC / 2A      |
| Dimension             | 190 x 82 x 30 mm |



Auto Focus



Low Light Verification



Long Distance Verification



Unaffected by High  
Temperatures 0° ~ 50°

Software

Desktop, Web, Cloud



Time Attendance



Access Control



Employee Self Service



Mobile App

**Disclaimer :** Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Certified by   

[www.biomaxsecurity.com](http://www.biomaxsecurity.com)

Connect with us on



BiomaxOfficial



BioMax Security



biomaxsecurity



BioMax Access Control