

## **2V DC 1.2A RFID Electric Bolt Lock Frameless Glass Door NC 5 cable Access control**



### **Specifications:**

1. Suitable For: 8-12mm Fully Frameless Glass Door
2. Fail Safe: Lock when energized(NC)
3. Cutout: 148Lx38Wx42H(mm)
4. Bracket:148Lx44Wx25H(mm)
5. Voltage: DC12V
6. Start Current: 900mA
7. Standby Current: 120mA
8. Solid Bolt: polishing housing, 1000kg Holding Force
9. Signal Output: Door Status Output,NO/COM



Abu Dhabi, UAE  
Tel: + 971 2 6229522  
Mob: +971 50 8596020  
Mail: info@bhartitec.com

10. Autolock Time Delay: 0,3,6secs.
11. Surface Temp: Low Temperature
12. Induction Distance: 10mm
13. Operating temp: -10~+25C(14-131F)
14. Operating Humidity: 0~90%(non-condensing)
15. Special Designed: Tested to 500000 operations
16. Face place material: High Aluminum, Carrulous Line Finished

**Package List:**

- 1 \* Electric Lock
- 1 \* Face Plate
- 1 \* Magnetic Base
- 1 \* Pack of Screws
- 1 \* User Manual (English)