



**F22**

## ➔ F22 - Ultra Thin Fingerprint Time Attendance & Access Control System

Display : 2.4-inch TFT LCD Color Screen

Fingerprint Capacity : 3000

Card Capacity : 5000(Optional) ID or mifare card

Transaction Capacity : 30,000

Sensor : BioID Sensor/ SilkID Sensor (optional)

Communication : RS232/485, TCP/IP,

USB-host,Wi-Fi

Access Control Interface : 3rd Party Electric Lock,

Door Sensor, Exit Button, Alarm

Wiegand Signal : Input, Output

Aux. Input : 1ea for linkage function

Functions : DST, Automatic Status Switch,

Record query, T9 input, 14 digit user ID,

Anti-passback, Scheduled-Bell, Printer(Optional),

ADMS(Optional)

Power Supply : 12V DC,3A

Operating Temperature : 0 °C- 45 °C

Operating Humidity : 20%-80%

Dimension(LxWxH) : 158.5x78.0x19.4mm

### Function

- 2.4-inch TFT color screen and Touch keys
- Ultra thin and elegant design
- Full Access Control Features: Anti-passback, access control interface for 3rd party electric lock, door sensor, exit button, alarm
- Standard Wi-Fi
- Network interface by TCP/IP or RS485
- Built-in auxiliary input with enhanced flexibility to link with wired detector or emergency switch
- Multiple Verification Modes: Multi-verification methods (card is optional) providing user various choices

