

N-K30



Finger



RFID



Inbuilt Battery



LAN



USB



Access Control

Time Attendance and Access Control

Storage Capacity

Finger Capacity	2000
Card Capacity	2000
Max User	2000
Password	2000
Log Capacity	1,50,000

Features

High-Speed and Accurate Fingerprint Identification

Fingerprint, Card, Password authentication

output relay for door open.

Good adaptation for dry, moist and rough fingerprints.

Supremely low Electric energy consumption.

Highly reliable and durable.

Comprehensive software development kit(SDK) is available for development and integration.



N-K30

"The Convenient
biometric Finger
verification."

N-K30

Communication Interface

Communication	TCP/IP, USB
---------------	-------------

Biometric

Push Data	YES
Sensor type	500 DPI
FAR	0.00001%
FRR	0.001%
OS	Linux
Verification time	<=1 second
RF card options	125kHz EM (Standard) / 13.56MHz Mifare (Optional)

Audio/Visual

LCD	2.4" TFT color screen
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English

Access control

Relay	YES
Support Exit Reader	Remote, Push Button, No Touch

Power & Environment

Inbuilt Battery Backup	YES
Operating Temperature	0°c ~ 50°c
Power	12V DC / 2A
Dimension	160 x 150 x 65 mm



Accepts moist and rough Finger



Accepts Color & Mahendi Finger



Compact & lightweight design



Unaffected by High
Temperatures 0° ~ 50°

Software

Desktop, Web, Cloud



Time Attendance



Access Control



Employee Self Service



Mobile App

Disclaimer : Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Connect with us on

- BiomaxOfficial
- BioMax Security
- biomaxsecurity
- BioMax Access Control