

APEXA® PRIME



Features




- Extremely Powerful and Future-Proof 7th Gen. Intel® Core™ i5 Processor
- 15" Bezel-Free True-Flat Display with PCAP Touch
- Ideal for Mission-Critical Applications in Retail and Hospitality Environments
- Sleek and Compact Body with Small Footprint
- Multiple I/O Interfaces for Peripherals
- Optional Powered USB for Peripheral Connections
- Designed for Countertop or Wall-Mount Solutions
- Faster Installation and Serviceability

Specifications

IT8786E		
System	Processors	Intel® Core™ i5-7200U (3M Cache, 3.10 GHz, 2 Cores) Intel® Pentium® 4405U (2M Cache, 2.10 GHz, 2 Cores)
	Chipset	ITE Tech IT8786E
	Memory	4GB Standard, DDR4L 2133 MT/s, Socket 1 x SODIMM (Max. 16GB)
	Storage	SATA 3 (6Gb/s) 2.5 inch SSD 64GB, Support AHCI
	Operating Systems	Windows 7, Windows 8.1, Windows 10 IoT Enterprise, POS Ready 7
	Audio	Realtek ALC662-VD
Display	Type	15" TFT LCD, LED Backlight
	Resolution	1024 x 768
	Brightness	300 cd/m² (typ.)
	Touchscreen	Projective Capacitive Touch
Interface	Display	1 x VGA (With Power Output)
	USB	6 (Rear 2, Back 4, USB 3.0 x 2, USB 2.0 x 4)
		3 (Reserved for MSR, SCR, i-Button / Touch Controller / Camera), RJ-45
	Serial	6 (COM 1 with 5V/12V Power Output on 9 Pins, BIOS) (COM2~3 RJ-45, Full Signal) (COM4 RJ-11, Only TX/RX, 12V Power Output, Reserved for CDP) (COM5 Reserved for Cash Drawer Port) (COM6 RJ-45, Only TX/RX, 5V Power Output, Reserved for MSR)
	LAN	1 x Gigabit Ethernet, RJ-45
	Audio	1 x Line-out
Power	Power DC-IN	1 x (3 Pin Connector)
	Extension Slot	Mini PCIe, m-SATA
	Power Supply	Adaptor 24V, 2A / 24V, 4A (Powered USB Option)
	Operating Temperature	0 °C ~ 60 °C at 10% to 90% Humidity
Physical & Environmental	Storage Temperature	-20 °C ~ 80 °C at 10% to 90% Humidity
	Dimensions (W x H x D)	364 x 333 x 210 (mm), 14.3 x 13.1 x 8.2 (in)
	Packing Dimensions (W x H x D)	500 x 470 x 300 (mm), 19.6 x 18.5 x 11.8 (in)
	Net Weight	5,300g, 11.6lbs
	Packing Weight	8,000g, 17.6lbs
	Certification	CE, FCC, KC, CB, CCC
	Color	Matte Dark Grey, High Gloss White
Options & Peripherals	2nd Displays	9.7", 12.1", 15" LCD Display, 1024 x 768, Optional Touchscreen
	Customer Display	VFD, 20 Columns x 2 Lines
	I/O Expansion	1 x COM5 (RJ-45 8 Pins) (Factory Option)
		1 x Cash Drawer Port (Factory Option)
		1 x Powered USB (24V)
	Storage	2.5 inch SSD 128GB, HDD 500GB, 1TB
	Magnetic Stripe Reader	Comply with ISO 7811, Support 1 & 2 & 3 Track
	Smart Card Reader	EMV Level 1, 2
	Dallas	Dallas i-button Reader
	Fingerprint	Yes
	Camera	5M USB Interface (Internal) (Factory Option)
	Wall Mount Kit	VESA-Compatible, 75 x 75 (mm), 100 x 100 (mm)
	Serial Conversion Cable	RJ-45 to D-sub 9
	Speaker	2 x 0.8W (Stereo)
	WiFi	Mini PCIe for Wireless LAN


Dimensions

Unit : mm



I/O Interfaces

IT8786E



- | | |
|-------------------------|---------------|
| ① COM 1 | ⑥ LAN |
| ② COM 2 | ⑦ USB 3.0 x 2 |
| ③ COM 3 | ⑧ VGA |
| ④ COM 4 | ⑨ MSR |
| ⑤ Power Connector / 24V | ⑩ AUDIO OUT |

Ordering Information

Part No.	Description
APEXA PRIME (G)	Intel Pentium 4405U, DDR4 4GB, SSD 64GB, 15" P-CAP Touch, Dark Grey, No O/S
APEXA PRIME (G)	Intel Core i5-6200U, DDR4 4GB, SSD 64GB, 15" P-CAP Touch, Dark Grey, No O/S
IPO-MS 237 C AX_G	MSR, Dark Grey
IPO-MS 237E2_SCR_AX	MSR + SCR, Dark Grey
IPO-MS 237DIB_AX_G	MSR + i Button, Dark Grey
APEXA_9.7 (G)	9.7" 2nd Display, Dark Grey, No Touch
APEXA_12.1 (D/G)	12.1" 2nd Display, Dark Grey, No Touch
APEXA_15 (D/G)	15" 2nd Display, Dark Grey, No Touch
APEXA_CDP (G)	Customer Display(VFD), Dark Grey
AXP-06 BRACKET_WALL MOUNT	Wall Mount

Peripherals



2nd Display
• 9.7", 12.1", 15" LCD



Customer Display
• VFD (2 Line x 20 Characters)



Card Reader
• MSR, SCR

POSBANK®

www.posbank.com sales@posbank.com

Copyright © 2018 POSBANK Co., Ltd.

POSBANK and the POSBANK logo are trademarks of POSBANK in the United States and other countries. All trademarks are the property of their respective owners. Intel, Celeron, Core are registered trademarks of Intel Corporation in the United States and other countries. Microsoft, Windows 7, Windows 8.1, Windows 10 IoT Enterprise and POS Ready 7 are registered trademarks of Microsoft Corporation in the United States and other countries. POSBANK shall not be liable for technical or editorial errors or omission contained herein. The information in this publication is informational purposes only and may be altered or amended by POSBANK. All statements regarding POSBANK's direction and intent are subject to change or withdraw without notice. Specifications may change without prior notice.