

Affordable Premium Performance



HT-4712

Advanced Compact POS Terminal

The HT-4712 is an advanced compact POS terminal, ideally suited for most retail sectors and cash till areas, where the space is at a premium. It brings greater value to the store owner through compact design, robust performance and superior consumer experience.

HT-4712

Small but Delicate

The integrated design of small footprint and rear cable cover, the HT-4712 not only frees the counter space but also keeps clutter-free, neat outlook.

Scalable Performance

The HT-4712 comes with multiple Intel CPU selection that ranges from Celeron all the way to Core i7, which delivers scalable performance for each unique need.

Expandable and Flexible

With a 12" tilt adjustable touch display and a wide range of peripheral options; the HT-4712 can be individually matched to various working counters.

Specification	HT-4712
Processor	Intel Haswell G1820 CPU, 2.70 GHz, 2M Cache; Intel Haswell G3320TE CPU, 2.30 GHz, 3M Cache; Intel Haswell Core i3-4330TE CPU, 2.40 GHz, 4M Cache; Intel Haswell Core i5-4570TE CPU, up to 3.30 GHz, 4M Cache; Intel Haswell Core i7-4770TE CPU, up to 3.30 GHz, 8M Cache
System Memory	DDR3L SO-DIMM x 2, max. 16GB
Storage Device	SATA x 2
Power Supply	12V/80W
OS Support	Windows 7/POSReady 7/Windows Embedded 8.1 Industry/Windows 10 IoT/Linux per request
Display & Touch	
LCD	12" TFT LCD
Resolution	1024 x 768
Touch	5-wire Resistive touch
I/O & Expansion	
Serial Port	4, DB9 x 4, optional COM5/COM6 via daughterboard, 5V/12V support on all COM ports
Parallel Port	Yes
Standard USB Port	8, USB 2.0 x 6 + USB 3.0 x 2
PoweredUSB Port	Optional 24V + 12V x 1 via daughterboard
LAN Port	10/100/1000 Mb x 1
Display Port	VGA x 1, DP x 1, 12V support on main VGA port for Posiflex monitors
CR Port	1, control 2 CR via optional Y-cable
PS/2 Port	Yes
Audio	Line-out/Mic-in, optional internal speaker x 1
Expansion Slot	PCIe slot x 1, via Riser card
Physical Dimension	
Dimension (W x D x H in mm)	295 x 264 x 341
Weight (N. W. in kg)	4
Environmental	
Operating Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD); 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)
Storage Condition	-20°C - 70°C, 10%RH - 90%RH

*Designed and Manufactured in Taiwan by Posiflex Technology, Inc.

*The product information and specifications are subject to change without prior notice.

*Please refer to the website for more attachment options.

Certifications	      	EN200525V3
----------------	--	------------

POSIFLEX

POSIFLEX TECHNOLOGY, INC.

No. 23, Datong St., Tucheng Dist., New Taipei City 23679, Taiwan
Tel : +886-2-2268-5577 E-mail : sales@posiflex.com.tw
Fax : +886-2-2268-5388 www.posiflex.com

Authorized Distributor / Reseller