
MT-4308W

Specification (Tablet only)	MT-4	308W	MT-4	4308W-4G
Processor	Intel Cherry Trail x5-Z8350 Quad Core CPU, up to 1.92 GHz, 2M Cache			
OS Support	Windows 10 IoT 32 bit & 64 bit			
LCD	1280 x 800, 8" TFT LCD with LED backlight			
Brightness	350 nits			
Touch Input	True-flat PCAP touch with multi-touch support			
System Memory	2GB DDR3L 4GB LPDDR3			3 LPDDR3
Storage Device	64GB eMMC			
Wireless Connectivity	Dual band 2.4 GHz/5.0 GHz, WiFi + BT; 3G NGFF (optional)			
Camera	8MP AF rear facing camera			
Speaker/Audio + Mic	Yes/Yes			
Sensor	G sensor, light sensor			
I/0	microSD, micro-SIM, Power Jack, micro-USB			
Button	Power			
Battery	4800 mAh			
Physical Dimension (Tablet only)				
Dimension (W x D x H in mm)	212 x 16.8 x 157			
Weight (N. W. in g)	550			
Environmental				
Operating Condition	0°C - 50°C, 20%RH - 90%RH			
Storage Condition	-20°C - 70°C, 10%RH - 90%RH			
Dock Station				
Model Name	DS-220	DS-320	DS-200	DS-300
Serial Port	DB9 x 2			
Standard USB Port	USB 2.0 x 3			
LAN Port	GigaLan x 1			
CR Port	1			
Built-in Printer	3" WiFi (dual band) thermal printer (200 mm/sec max.)		N/A	
Tablet Charging	Yes			
Built-in Options				
3G Communication	Selected	l band		
Attachment Options				
MSR [TA-220 / TA-300]	3T MSR reader			
RFID (TA-220)	Support MIFARE Classic 1K & MIFARE Ultralight			
Scanner	2D barcode scanner embedded in Pistol Grip			
Pistol Grip (PG-201E)	Swappable battery module (5000 mAh) & optional 2D barcode scanner			
Shoulder Strap + 2 nd Battery Option (TA-500)	Swappable battery module (5000 mAh)			
Fingerprint sensor [TA-300]	Fingerprint Sensor (Active Capacitive technology)			
Standalone Options				
Removal Battery Charging Rack (CS-100)	Charging rack for up to 4 x removal battery			
Quad Tablet Charging Rack (CS-200)	4 slots tablet charger for charging up to 8" tablet x 4			
Tablet Charging Rack (CS-210 / CS-220)	Single charging station for MT Series tablet			
Hand Strap	Hand Strap is available for added security			



* Designed and Manufactured in Taiwan by Posiflex Technology, Inc. * The product information and specifications are subject to change without prior notice. * Please refer to the website for more attachment options.





The Best Companion for Mobile Retailing and Hospitality

MT-4308W

Ergonomic and Versatile Mobile POS




Protection Cover (MC-408)

FC

POSIFLEX TECHNOLOGY, INC. No. 23, Datong St., Tucheng Dist., New Taipei City 23679, Taiwan Tel: +886-2-2268-5577 E-mail: sales@posiflex.com.tw Fax : +886-2-2268-5388 www.posiflex.com

Authorized Distributor / Reseller







Adoptable yet Durable

With durability to survive up to 1.5 meters drop, the MT-4308W is a rugged Windows tablet designed to meet any business applications.

Multi-use Versatility

MT-4308W with the patented pistol grip

are tailored for service on the go, suited

for inventory, line busting, ticket taking,

loyalty programs, and many more.



Patented Pistol Grip (U.S. Patent 9436226 B2)

The optional patented pistol grip is ergonomically designed for easy carrying and houses a removable battery to vastly extend the overall operating time.



Transform with Dock Station

MT-4308W can transform into an all-in-one desktop POS terminal with the optional docking station that integrates a built-in 3" WiFi thermal printer.

ATTACHMENT



MC-408 For 8" tablet



TA-220 Side attahcment of MSR and/or RFID



TA-300 Side attahcment of MSR and/or Fingerprint Sensor



TA-500 Additional 5000 mAh battery attachment for Hospitality Package with shoulder strap



CS-210/CS-220 Single charging station/ Single charging station with LAN port and USB2.0 x 2 port



DS-200 Dock Staion with USB x 3, COM x 2. LAN and CR



CS-100 4 slots battery charger for charging up to RB-3000 battery x 4



CS-200 4 slots tablet charger for charging up to 8" tablet x 4







Hand Strap Hand Strap is available for added security



PG-201E

Pistol Grip shaped handheld with 5000 mAh battery built-in and optional 2D barcode scanner for Retail Package



DS-300



DS-220 DS-320 Dock Staion with 3" WiFi thermal printer,

USB x 2, COM x 2, LAN and CR