

RT-2015/2016

Specification		RT-2015	RT-2016
Processor	Intel Bay Trail J1900 Quad Core CPU, up to 2.42 GHz, 2M Cache		
System Memory	DDR3L SO-DIMM slot x 1, max. 8GB		
Storage Device	SATA x 2		
Power Supply	12V/60W		
OS Support	Windows 7/POSReady 7/Windows Embedded 8.1 Industry/Windows 10 IoT/Linux per request		
Display & Touch			
LCD	15" TFT LCD	15.6" TFT LCD	
Resolution	1024 x 768	1920 x 1080	
Touch	True-flat PCAP touch with multi-touch support (IP65 on front panel)		
I/O & Expansion			
Serial Port	3, DB9 x 1 + RJ50 x 2, 5V/12V support on all COM ports		
Standard USB Port	5, USB 3.0 x 1 + USB 2.0 x 4		
PoweredUSB Port	Optional Powered USB module with 24V + 12V (USB 3.0 x 1 will no longer be available with the Powered USB module)		
LAN Port	10/100/1000 Mb x 1		
Display Port	VGA via proprietary connector (12V support for Posiflex monitors) x 1+ mini DP x 1		
CR Port	1, control 2 CR via optional Y-cable, supporting 24V cash drawer		
Audio	Internal 2W speaker x 1		
Expansion Slot	M.2 slot x 1		
Physical Dimension			
Dimension (W x D x H in mm)	368 x 207 x 325	402 x 207 x 297	
Weight (N. W. in kg)	5.4	5	
Environmental			
Operating Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD); 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)		
Storage Condition	-20°C - 70°C, 10%RH - 90%RH		
Built-in Options			
WiFi	M.2 WiFi/BT module		
Camera	1MP wide angle camera		
AG Glass	Cannot coexist with built-in camera		
UPS Battery Backup	UPS pack for RT Series		
Attachment Options			
POS Monitor	9.7"/10.1" TFT LCD display (touch/non-touch)		
Line Display	2 x 20 rear-mount VFD customer line display		

*Designed and Manufactured in Taiwan by Posiflex Technology, Inc.
*The product information and specifications are subject to change without prior notice.
*Please refer to the website for more attachment options.

Certifications

FC

CE

SGS

UL

UL

UL

RoHS

REACH

Windows Embedded

Partner

EN200701V6

POSIFLEX

POSIFLEX TECHNOLOGY, INC.

No. 23, Datong St., Tucheng Dist., New Taipei City 23679, Taiwan

Tel : +886-2-2268-5577 E-mail : sales@posiflex.com.tw

Fax : +886-2-2268-5388 www.posiflex.com

Authorized Distributor / Reseller

Make Your Business Look More Attractive

RT-2015/2016

Fanless POS Terminal

The **RT-2000 Series** radiates in its new design – featuring an ultra-slim and sleek look that exhibits elegance. It is uncompromising to the space requirements and provides better cable management and easy maintenance. The new RT-2000 Series is taking POS terminal design into the next level, setting your brand image apart from the others.



Full HD
15.6"

Slim & Stylish Look

With stylish, fluid contours for its base and true-flat design, the RT-2000 Series has 15" or 15.6" PCAP touch screen, and full suite of ports that are hidden in the clean rear cover. No screws can be found on its surface maintaining a neat and sleek look.

Patented Fanless Technology

The patented fanless technology allows the terminal to run quietly in all kinds of harsh conditions and – at the same time - provides a long service life.



Fanless
Technology



Dust
Resistant



Water
Resistant



Money
Saving



Clean Cable Management

Advanced cable management design delivers a truly clutter-free station. The standard base can house the optional PoweredUSB or USB extension module, while the optional base integrates a UPS backup (RB-5000) for the event of a power failure.



Expandable
USB Module

Serviceability & Shipment with Ease

Rear cover can be removed easily and without tools, thus allowing for faster installation and serviceability. The unit can be shipped with line display or 9.7" /10.1" 2nd customer facing LCD display attached and folded, saving deployment time as well as shipping costs.

