


# EaZy-Q<sup>®</sup>

## EQ-LDxxE

### Smart LED Displays

#### Multi-Function:

- ✓ Counter Display (Queue System)
- ✓ Multimedia Play-List
- ✓ Customer Information
- ✓ Corporate Messaging
- ✓ In-house Promotions
- ✓ 3<sup>rd</sup> Party Advertisements
- ✓ Live Dashboard
- ... and more



Technical Specifications – EQ-LDxxE						
Model	EQ-LD10TE	EQ-LD11E	EQ-LD12E	EQ-LD13E	EQ-LD16E	EQ-LD19E
Display Size	10.1"	11.5"	12.1"	13.3"	15.6"	18.5"
Touch-Screen	Yes (Built-in)	Optional				
Display Type	IPS LED					
Effective Visible Angle	170°/170°					
Resolution	1024x600	1280 x 800				1920 x 1080
Max. Number of Units (Central Management)	Up to 65,536 under Single Control (Depending upon No. of Channels for the Central Mgmt. Software)					
OS	Android (Standard) / Linux (Optional)					
Modes of Operation (Multi-Function Capability)	<ul style="list-style-type: none"> <li>◆ Counter Displays for Queue Management System</li> <li>◆ Digital Signage / Promo Displays (Can Manage Multiple Playlists)</li> <li>◆ Meeting Room Display (with Management of Multiple Schedules)</li> <li>◆ Customer Information (General Guidance / Interactive)</li> <li>◆ DID - Digital Information Display (Inside &amp; Outside the Elevators)</li> <li>◆ In-house &amp; 3<sup>rd</sup> Party Promotions (Videos / Pictures / Messages)</li> <li>◆ Live Dashboard (For Administrator / Operations Manager)</li> <li>◆ Quick Instructions Displays (to Warehouse, Stores, Kitchen, etc.)</li> <li>◆ EQ-LD10TE can also be used as <u>Touchpad-Calling-Terminal</u> and/or <u>C.F.S.</u></li> <li>◆ .... And more</li> </ul>					
Response Time	50 to 100 Milliseconds					
Available Storage Memory	Standard 4GB (Upgradeable to 32GB)					
Communication Ports	Wi-Fi & Ethernet	Wi-Fi, Ethernet & PoE				Wi-Fi & Ethernet
Optional Comms.	BT / 3G	Bluetooth / 3G / NFC				
Audio	Built-in Stereo Speakers (with MP3 / WMA play option)					
Pictures / Video Option	JPG / JPEG / MPEG1 / MPEG 2 / MPEG 4 / AVI					
Languages Supported	English, French, German, Italian, Spanish, Arabic, Portuguese, Dutch and more					
Storage Temperature	-20°C to 60°C					
Storage Humidity	20% to 85% (Relative)					
Operating Temperature	5°C to 45°C (Ideal Temp. = Between 15°C to 35°C)					
Power Supply	12V DC 2 AMP					
Life Span	60,000 to 80,000 Hours [Approximately 8 to 10 Years] (Life Span may vary depending upon the Environmental Conditions)					