



Multi-Function:

- ✓ Queue System Display
- ✓ Multimedia Play-List
- ✓ Customer Information
- ✓ Corporate Messaging
- ✓ In-house Promotions
- ✓ 3rd Party Advertisements g_□
- ✓ Live Dashboard

.... and more



Brands

www

EaZy-Q®





omer Call Center at 1-416-999 9999



| Technical Specifications – EQ-BDxx | | | |
|---|--|----------------------|------------------------------|
| Model | EQ-BD06 | EQ-BD06A | EQ-BD07A |
| Processor | Dual-Core | Quad-Core | Octa-Core |
| RAM | 512 MB | 1 GB | |
| Built-in Memory | 4 GB | 8 GB | |
| Maximum Built-in Memory Capacity | Up to 32 GB | Up to 64 GB | Up to 128 GB |
| External HDD Support | Up to 2 TB HDD via External USB Port | | |
| Max. Number of Units | Up to 65,536 under Single Control | | |
| (Central Management) | (Depending upon No. of Channels for the Central Mgmt. Software) | | |
| Modes of Operation (Multi-Function Capability) | As Main Display for Queue Management System | | |
| | Multimedia Player (Can Manage Single or Multiple Playlists) | | |
| | Customer Information (General / Interactive) | | |
| | Notice Board & Event Management (at Main Entrance / Hotel Lobby) | | |
| | Corporate Messaging (Floors / Area Wise) | | |
| | In-house & 3rd Party Promotions (Videos / Pictures / Messages) | | |
| | Live Dashboard (For Administrator / Operations Manager) | | |
| | Quick Instructions Display (to Warehouse, Stores, etc.) and more | | |
| Display Proportion | 16:9 / 4:3 (User Definable) | | |
| Graphic Display | | Full-HD 1920x1080 | Ultra HD – 4K |
| | High Definition | (including Mali 400 | (Including Mali 400+ |
| | | Graphic Accelerator) | Graphic Accelerator) |
| Video Streaming Support | At Low Definition | At High-Definition | |
| Video Support Formats | H.263 / H.264 / H.265 (EQ-BD07A) / VC-1 / WMV / DV / XVID / VP6,8 / MPEG1,2,4 / RM / REAL(RMVB) / FLV / MOV / VOB / AVI / MKV / M2TS / F4V/ ASF / 3GP | | |
| Audio Support Formats | MP3 / WMA / APE / Flac / WMA / 3GP / AAC / | | |
| | ADPCM / AMR / M4A / MID / OGG / PCM / WAV | | |
| I/O Interface | HDMI / Cabled Ethernet / Wi-Fi / USB / USB-OTG | | |
| | Bluetooth (Optional) / 3G (Optional) | | |
| Storage Temperature | -20°C to 60°C | | |
| Operating Temperature | 5°C to 45°C | | |
| Power Supply | 5V DC 1Amp | | |
| | | MATRIX | 1929 Markham Boad, Suite #20 |

