



Teller Station Units

EQ-CD6S/6W

EQ-CD6T

EQ-LD10TE

- ✓ Touch-Screen
- ✓ Web Based
- ✓ Client-Server Based



Technical Specifications	EQ-LD10TE (Industrial Grade)	EQ-CD6T (Standard)	EQ-CD6W Web Based	EQ-CD6S C/S Based
Device Type	Tablets (Hardware)		Virtual (Software)	
User-Interface	Multi-Touch	Touch	Web-Based	C/S Based
Screen Size	10.1-inch	7-inch	N/A (Based on Client/User PC)	
Communication Interface	Built-in Wi-Fi & Ethernet	Wi-Fi (Built-in) Ethernet (Optional)	N/A (Works on LAN / WAN / VPN / Internet)	
Number of Keys	Over 35 (User Definable)			21 to 25 (Customizable)
Supported O/S	Android (Standard) Linux & iOS (Optional)		N/A Any Browser	Win XP / Vista / 2000 / 7 / 8 / 10
Features / Functions	<ul style="list-style-type: none"> ✓ User Login & Logout ✓ Next & Re-Call ✓ Manual-Call (Out of Sequence - with Pre-Authorization Control) ✓ Finished / Served (with Auto-Finish upon Next, Short-Break and / or Logout) ✓ Advance Transfer Features (Auto & Manual with Single / Multiple Transfers) ✓ Put Token on HOLD (with Reason) and / or Delay Token for Specified Duration ✓ Cancel and Re-Activate Tokens ✓ Short Break Facility (User-Definable) ✓ Waiting Customers Inquiry (Overall / Service Category Wise) ✓ Call Manager for Support ✓ Calling Office Boy / Request Coffee / Water / Tea, etc. (User-Definable) ✓ Send Pre-Defined Messages to Other Calling Devices ✓ Assisted Token Issuance (Direct Command to Dispensers for Issuing Tokens) ✓ Multiple Counters and / or Rooms Management using Single-Calling Terminal ✓ ... and more 			
Maximum Devices per Location	512 (on LAN) / 65K (over VPN) Unlimited (Over Internet)			
3G / GSM Support	Optional		N/A	
Smart Auto-Correction	Auto-Debugging & Reset (Without Stopping the System in Operation)			
Dimensions	262 x 173 x 29 mm	126 x 77 x 7 mm	N/A	
Body Color	Black	Black White (Optional)		
Storage Temp.	0° to 60°C			
Operating Temp.	5° to 48°C	5° to 40°C		
Power Supply	12V 1.5A	5V 0.8A		