

METAL DETECTORS

VV-MD33Z-DFPU2 DOOR FRAME METAL DETECTOR



FEATURES

33 Zones Omnidirectional Detection with Adjustable Sensitivity

Up to 99 Sensitivity Levels for Each Zone

30 Preset Programs for Security Application

Automatic Bidirectional Pass & Alarm Counter

7" Color LCD Display Screen

Simultaneous Multi-Zone Alarm Supported

Supports Buzzer Alarm and Multi-Zone LED Indicator

TECHNICAL SPECIFICATIONS

VV-MD33Z-DFPU2

Parameter	Specifications
Detection Zones	33 zones detection sensitivity against ferrous, non-ferrous & alloy objects
Construction	High density ABS coated panel
Passage Dimension	Height: 2200mm approx. Breadth: 800mm approx
Display	7" LCD control panel for real-time statistics & alarm counter
Alarm	Supports multi-zone bi-directional alarm buzzer & LED indicators
Sensitivity	99 levels adjustable sensitivity for each zone
Calibration	Automatic
Detection Level	30 preset programs
Throughput rate	25 people per minute
Multi-Zone Detection	Supports simultaneous alarm from multiple zones
Protection	Conforms to relevant electrical safety standard
Power Supply	AC100-240V, <15W
Battery Backup	Supports 4 - 5 hours (Optional)
Working Environment	-20°C -50°C
Working Frequency	4KHz - 8KHz
Machine Weight	Approx. 70Kg
Dimensions	2200mm (height) x 800mm (width) x 580mm (depth)
Certifications	CE, FCC, RoHS

*Exact products and specifications shown may vary by geographic region and are subject to change without notice. Weights and measurements are approximate and may vary.

VANTAGE INTEGRATED SECURITY SOLUTIONS LIMITED

B3, Bredon House 321, Tenttenhall Road Tettenhall, Wolverhampton

West Midlands, WV6 0JZ United Kingdom

Ph: +44-1902793383, Email: sales@vantagesecurity.com

www.vantagesecurity.com

(AN ISO 9001 : 2008, ISO14001 : 2004 CERTIFIED COMPANY)

