



TF 1700

➔ Standalone Fingerprint Time Attendance & Access Control System - IP 65

Fingerprint Templates : 3000
 Card Storage : 3000
 Transaction Storage : 50,000 Logs
 Card Reader : Yes
 CPU : 400MHz
 Fingerprint Sensor : 500 DPI Optical sensor
 (Optional Secugen STQC certified sensor)
 FAR : $\leq 0.0001\%$ / FRR : $\leq 1\%$
 Identification Speed : ≤ 1 Sec
 Algorithm Ver : 10
 Display : 128 x 64 OIED with white Color
 Keypad : 4 x 4 Keypad
 Schedule Bell/Speaker : Mini Speaker
 Communication : RS485 , TCP/IP , USB-host
 Push data : NO
 Standard Features : DLST
 Power Supply : DC 12V: 1.5Amp
 Operating Temperature : 0°C to 45°C
 Operating Humidity : 20% -80%
 Dimension : 90 x 190 x3.5 mm
Access Control : Wiegand : In & Out
 both 26 or 34 bit (With or without site code)

Relay : 12 V relay for lock EM lock,
 Bolt Lock or Strike lock
 Support Fire Alarm : Yes / Door Sensor ; Yes
 Anti Passback : Yes / Door Bell : Yes
 Support exit reader : KR500,101 HE
 Battery : No / Card Readers : Yes
 Communication : No
 Sensor : Mifare

Compatibility :

- Compatible with Multi Door controllers via weigand
- External Speaker output available (Optional)
- External Bulb output available (Optional)

Compatible Software & SDK :

- Etime track lite desktop & web
- SDK for desktop applications
- Web based Device Manager/ePush server using Push data. Helps developers & integrators
- Supports 3rd Party Payroll/HRMS/ERP and Other applications